


Datasheet

TAU3632-8BC44-2EA0



Output power	10,0 kVA
Input	Y500-400/D289-230 V AC
Output	Y 400 / D 230 V AC
Category	Line, Control circuit und Isolation transformer



Picture representative

Electrical parameters

Phases	3
Nominal power	kVA 10,0
Short-time power	kVA 33,0
Nominal input voltage	V AC 500-400-289-230
Nominal input current	A AC 12,1-15,1-20,9-26,3
Nominal output voltage	V AC 400-230
Nominal output current	A AC 14,4-25,0
Frequency	Hz 50...60
Short circuit voltage	% 3,32 20°C
Vector group	IIIiii0
Duty	continuous
Duty cycle	% 100
Winding material	CU
Winding losses	W 470
Iron losses	W 100
Total losses	W 570
Efficiency	% 94,7

Standards


Standards	EN 61558-2-1, -2-2, -2-4 UL 1561 / XQNX2-8.E103902
-----------	---

Authorization / Certificate

Approvals	ENEC cULus (further approvals possible on customer request)
Declaration of Conformity	CE

Environmental conditions

Operating temperature	°C	-25 ... +40
Storage temperature	°C	-25 ... +55
Extended temperature range	°C	up to +80 (after power reduction according to the load characteristics)



Relative humidity (without condensation)	%	5 ... 95
Cooling		natural cooling
Installation altitude		to 1000m above sea level, higher altitude possible with power reduction
Overvoltage category	(acc. EN 61558)	OVC III
Degree of pollution	(acc. EN 61558)	P2


Installation and mounting

Type of terminals	Screw connection
Mounting type	Screw
Mounting position	see „Dimensional drawing“ at the end of the document
Dimensions (HxWxD)	see „Dimensional drawing“ at the end of the document
Mounting dimensions	see „Dimensional drawing“ at the end of the document
Oblong hole	see „Dimensional drawing“ at the end of the document
Clearance distance	see technical information in the chapter „Further information“

Security features

Insulation class	acc. EN	class H
Insulation class	acc. UL	CLASS 180
Protection		IP00 (other types of protection on request)
Protection class		I
Short-circuit strength		conditionally with protection

Connection table



Terminal block

Back side: -----

Front side:

1U1-1U1-1U3-1U2-1V1-1V1-1V3-1V2-1W1-1W1-1W3-1W2 2U1-2U1-2U2-2V1-2V1-2V2-2W1-2W1-2W2

	U _N [V AC]	I _N [A AC]	Terminals 	Wiring 	Protection
PRI1	500	12,1	1U1-1V1-1W1	1U2-1V2-1W2	3RV2411-4AA10 / 13,5A (ext.)
	400	15,1	1U1-1V1-1W1	1U3-1V3-1W3	3RV2421-4BA10 / 17,0A (ext.)
	289	20,9	1U1-1V1-1W1	1U1-1W2 1V1-1U2 1W1-1V2	3RV2431-4EA10 / 24A (ext.)
	230	26,3	1U1-1V1-1W1	1U1-1W3 1V1-1U3 1W1-1V3	3RV2431-4PA10 / 30A (ext.)
SEC1	400	14,4	2U1-2V1-2W1	2U2-2V2-2W2	3RV2011-4AA10 / 14,5A (ext.)
	230	25,0	2U1-2V1-2W1	2U1-2W2 2V1-2U2 2W1-2V2	3RV2021-4NA10 / 26A (ext.)



NOTE protection

Protection acc. IEC 60947 | Type suggestion with Siemens circuit breaker - alternatives are possible.
Protection for the North American market acc. UL - see chapter „Further information“.

General data

GTIN / EAN	4052967065314
Country of origin	Czech Republic
Packaging unit	1
Export sign	AL: N / ECCN: N
Customs tariff number	85043200
Gross weight - brutto	kg 77
Net weight - netto	kg 65

Further information

Complete catalogue Transformers / Power Supplies / Reactors / Filters

www.mdexx.com/online-katalog

Core product range Transformers

www.mdexx.com/core-products-range-transformers

Technical information

www.mdexx.com/technische-information

ePLAN / CAD data

www.eplandata.de/portal/en_EN/part/MDX.TAU3632-8BC44-2EA0

Service / Support

- Operating instruction [www.mdexx.com/BA_T_Transformatoren\(TAM,TAP,TAT,TAU,TBT,TBU\)](http://www.mdexx.com/BA_T_Transformatoren(TAM,TAP,TAT,TAU,TBT,TBU))
- Certificate www.mdexx.com/downloads/zertifikate
- EU Declarations of Conformity [www.mdexx.com/Transformatoren nach EN 61558\(TAM,TAN,TAP,TAT,TAU,TAW\)](http://www.mdexx.com/Transformatoren nach EN 61558(TAM,TAN,TAP,TAT,TAU,TAW))
- EAC Certifications www.mdexx.com/EAC_Transformatoren

- UL Certifications

US	product	www.mdexx.com/XONX2.E103902 (TEM, TEP, TET, TEU, TAN, TAP, TAT, TAU, TBT, TBU)
	isolation	www.mdexx.com/OBJY2.E106597 (CTB130, CTB155, ADS180, CCC180)
CA	product	www.mdexx.com/XONX8.E103902 (TEM, TEP, TET, TEU, TAN, TAP, TAT, TAU, TBT, TBU)
	isolation	www.mdexx.com/OBJY8.E106597 (CTB130, CTB155, ADS180, CCC180)

Dimensional drawing

